

# FRIGIDAIRE

GALLERY



## Side-by-Side Refrigerator

FGHC2344K F

23 Cu. Ft. Counter-Depth



### Signature Features



#### Most Usable Shelf Space<sup>1</sup>

Our adjustable shelves have room to store more.



#### SpaceWise™ Organization System

Our SpaceWise™ Organization system makes it easy to keep food organized and easy to find when you need it.



#### Real Stainless Steel

Real stainless steel with a protective coating that reduces fingerprints and smudges so it's easy to clean.



#### Best-in-Class Ice & Water Filtration<sup>2</sup>

PureSource Ultra™ Water Filtration offers best-in-class water filtration so you get cleaner, better-tasting water at your fingertips.

### Powerful Performance

PureAir Ultra™ Filters  
Energy Saver Plus Technology  
Quiet Pack

### Performance-Driven Style

Express-Select™ Controls  
Designer Lighting  
Tall, 7-Button Water & Ice Dispenser  
Digital Electronic Temperature Controls  
Textured Cabinet

### SpaceWise™ Design

Refrigerator –  
2 Sliding SpillSafe™ Glass Shelves  
Fixed SpillSafe™ Glass Shelf  
Chill Drawer  
2 Clear Crispers with Adjustable Humidity Controls  
Wine Rack/Can Dispenser  
2 Adjustable Clear 2-Liter Door Bins  
Fixed Clear Gallon Door Bin  
Clear Condiment Bin  
Freezer –  
2 Fixed Wire Shelves  
Space-Saver Shelf  
2 Tall Wire Baskets  
3 Clear Fixed Door Bins  
Tilt-Out Wire Door Shelf

ENERGY STAR®  
Sabbath Mode (Star-K® Certified)



### Capacities

Total Capacity	22.6 Cu. Ft.
Refrigerator Volume	14.1 Cu. Ft.
Freezer Volume	8.5 Cu. Ft.

### Overall Exterior Dimensions

Height (Including Hinges & Rollers)	69-3/8"
Width	35-5/8"
Depth	26-7/8"


### Available in:

Stainless  
(F)

<sup>1</sup>As compared to other counter-depth side-by-side models.

<sup>2</sup>As compared to other consumer refrigeration water filtration systems.

frigidaire.com



### Side-by-Side Refrigerator Specifications

- Product Shipping Weight (approx.) – 325 Lbs.
- Voltage Rating – 120V/60 Hz/15 or 20 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.02 kW  
(For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 8.5 Amps
- Always consult local and national electric & plumbing codes.
- Floor should be level surface of hard material, capable of supporting fully loaded refrigerator.
- When installing refrigerator adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 120° to 180° door swing, providing complete drawer/crisper access and removal. (*Absolute 4-1/2" minimum clearance will ONLY allow for 90° door swing which will provide drawer/crisper access with restricted removal.*)
- To ensure optimum performance, avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.
- For proper ventilation, front grille MUST remain unobstructed.
- Recess electrical outlet when possible.
- Water recess on rear wall recommended to prevent water line damage.
- Water Pressure – Cold water line must provide between 30 and 100 pounds per square inch (psi).
- Copper tubing with 1/4" O.D. recommended for water supply line with length equal to distance from rear of unit to household water supply line plus 7 additional feet. Optional Water Supply Installation Kits available.
- Adjustable front rollers to assist with door alignment.

### "Built-In Look" Specifications

- Minimum opening of 70-1/4" H x 36" W x 25" D required to allow for ease of installation, proper air circulation, and plumbing/electrical connections.
- Remove all wall/floor molding prior to installation.

**Note:** For planning purposes only. Refer to Product Installation Guide on the web at [frigidaire.com](http://frigidaire.com) for detailed instructions.